



AU9464865

(12) PATENT ABSTRACT (11) Document No. AU-A-64865/94
(19) AUSTRALIAN PATENT OFFICE

(54) Title
COMMUNICATION SYSTEM WITH ISDN AS A BACKUP OF INTER-PBX TIE TRUNK

International Patent Classification(s)
(51)⁵ **H04Q 011/04 H04L 012/52 H04Q 003/66**

(21) Application No. : **64865/94** (22) Application Date : **21.06.94**

(30) Priority Data

(31) Number	(32) Date	(33) Country
5-172126	21.06.93	JP JAPAN
5-172127	21.06.93	JP JAPAN

(43) Publication Date : **22.12.94**

(71) Applicant(s)
NEC CORPORATION

(72) Inventor(s)
MAKOTO HOKARI

(74) Attorney or Agent
SPRUSON & FERGUSON , GPO Box 3898, SYDNEY NSW 2001

(57)

A private branch exchange (1) comprises a switch (10) to which are connected line interfaces (13) accommodating PBX telephones (5), a tie trunk interface (11) accommodating a tie trunk (3) to a distant PBX (2), an ISDN interface (12) accommodating the public switched ISDN network (4), and speech codecs (14). Each codec (14) converts a 64-kbps signal to a lower bit-rate signal and converts a lower bit rate signal to a 64-kbps signal. A mux/demux unit (16) is connected between the codecs (14) and the switch (10) for multiplexing the lower bit rate signals from the codecs (14) into a multiplex signal and demultiplexing a multiplex signal into lower bit rate signals for coupling to the codecs (14), respectively. The switch (10) is controlled in response to a call from a PBX telephone (5) to establish a connection between a line interface (13) and any of the codecs (14) and a connection between the mux/demux unit (16) and the tie trunk interface (11) when the distant PBX (2) is the destination. If the call is destined to an ISDN user, a connection is established between the line interface (13) and the ISDN interface (12). Should the tie trunk (3) fail, a backup connection is established between the mux/demux unit (16) and the ISDN interface (12) and the ISDN network (14) is signalled to establish a connection between the ISDN interface (12) and the distant PBX (2).

(11) 64865/94

-2-

CLAIM

1. A private branch exchange comprising:

- switch means;
- a plurality of line interfaces connected the switch means for accommodating user telephones;
- a tie trunk interface connected to the switch means for accommodating a tie trunk connected to a distant private branch exchange (PBX);
- an ISDN (integrated services digital network) interface connected to the switch means for accommodating a public switched ISDN network;
- a plurality of bit-rate compression/expansion means connected to the switch means, each of the bit-rate compression/expansion means converting a 64-kbps digital signal to a digital signal of a bit rate lower than 64-kbps and converting a said lower bit rate digital signal to a said 64-kbps digital signal;
- mux/demux means connected between said plurality of bit-rate compression/expansion means and the switch means for multiplexing the lower bit rate digital signals from the bit-rate compression/expansion means to produce a multiplex signal and demultiplexing a said multiplex signal into a plurality of lower bit rate digital signals and applying said plurality of lower bit rate digital signals to said bit-rate compression/expansion means, respectively; and
- control means associated with said line interfaces, said tie trunk interface and said ISDN interface for controlling said switch means in response to a call from a said user telephone to establish a connection between the line interface of the said user telephone and any of the bit-rate compression/expansion means and a connection between the mux/demux means and the tie trunk interface when said call is destined to the distant PBX, or a connection between the said line interface and the ISDN interface when said call is destined to a user telephone of the ISDN network, the control means monitoring the tie trunk interface for detecting a failure in the tie trunk and, in response, establishing a backup connection between the mux/demux means and the ISDN interface, instead of the connection between the mux/demux means and the tie trunk interface, and causing the ISDN network to establish a connection between the ISDN interface and the distant PBX.

